



## Composición de referencias de producto Kampsy

IRC	Flujo LM	Regulable	Tcc	° Óptica	Montaje	Color	Referencias
80	2880LM	NR	3000K	SIM	SUSPENDIDO	BLANCO / NEGRO / GRIS	622.80.288.NR.30.30.SP.BL
							622.80.288.NR.30.30.SP.GR
							622.80.288.NR.30.30.SP.NE
		DD	3000K				622.80.288.DD.30.30.SP.BL
							622.80.288.DD.30.30.SP.GR
							622.80.288.DD.30.30.SP.NE
	3000LM	NR	4000K				622.80.300.NR.40.30.SP.BL
							622.80.300.NR.40.30.SP.GR
							622.80.300.NR.40.30.SP.NE
		DD	4000K				622.80.300.DD.40.30.SP.BL
							622.80.300.DD.40.30.SP.GR
							622.80.300.DD.40.30.SP.NE
3040LM	NR	5000K	622.80.304.NR.50.30.SP.BL				
			622.80.304.NR.50.30.SP.GR				
			622.80.304.NR.50.30.SP.NE				
	DD	5000K	622.80.304.DD.50.30.SP.BL				
			622.80.304.DD.50.30.SP.GR				
			622.80.304.DD.50.30.SP.NE				
90	2880LM	NR	3000K	622.90.288.NR.30.30.SP.BL			
				622.90.288.NR.30.30.SP.GR			
				622.90.288.NR.30.30.SP.NE			
		DD	3000K	622.90.288.DD.30.30.SP.BL			
				622.90.288.DD.30.30.SP.GR			
				622.90.288.DD.30.30.SP.NE			
	3000LM	NR	4000K	622.90.300.NR.40.30.SP.BL			
				622.90.300.NR.40.30.SP.GR			
				622.90.300.NR.40.30.SP.NE			
		DD	4000K	622.90.300.DD.40.30.SP.BL			
				622.90.300.DD.40.30.SP.GR			
				622.90.300.DD.40.30.SP.NE			
	3040LM	NR	5000K	622.90.304.NR.50.30.SP.BL			
				622.90.304.NR.50.30.SP.GR			
				622.90.304.NR.50.30.SP.NE			
		DD	5000K	622.90.304.DD.50.30.SP.BL			
				622.90.304.DD.50.30.SP.GR			
				622.90.304.DD.50.30.SP.NE			