



## Composición de referencias de producto Milos

Descripción	IRC	Flujo LM	Regulable	Tcc	° Óptica	Montaje	Color	Referencias
MILOS 120 UGR<19	80	1060LM	NR	3000K	60	EMPOTRADO	BLANCO	526.80.106.NR.30.60.EM.BL
					90			526.80.106.NR.30.90.EM.BL
		1110LM	NR	4000K	60			526.80.111.NR.40.60.EM.BL
					90			526.80.111.NR.40.90.EM.BL
MILOS 170 UGR<19	80	1110LM	NR	3000K	60			527.80.111.NR.30.60.EM.BL
					90			527.80.111.NR.30.90.EM.BL
		1120LM	NR	4000K	60			527.80.112.NR.40.60.EM.BL
					90			527.80.112.NR.40.90.EM.BL
		2130LM	NR	3000K	60	527.80.213.NR.30.60.EM.BL		
					90	527.80.213.NR.30.90.EM.BL		
		2210LM	NR	4000K	60	527.80.221.NR.40.60.EM.BL		
					90	527.80.221.NR.40.90.EM.BL		
MILOS 225 UGR<19	80	2200LM	NR	3000K	60	528.80.220.NR.30.60.EM.BL		
					90	528.80.220.NR.30.90.EM.BL		
		2250LM	NR	4000K	60	528.80.225.NR.40.60.EM.BL		
					90	528.80.225.NR.40.90.EM.BL		
		3070LM	NR	3000K	60	528.80.307.NR.30.60.EM.BL		
					90	528.80.307.NR.30.90.EM.BL		
		3180LM	NR	4000K	60	528.80.318.NR.40.60.EM.BL		
					90	528.80.318.NR.40.90.EM.BL		